











Ergo Line Combo

Hot + Hot

Ergo Line Combo is a light weight, but robust, cart for holding and transportation of hot food with GN1/1 capacity. Detachable U-shaped runners offer safe handling, easy cleaning and optimal temperature distribution. Infinitely variable temperature setting is performed via digital displays which indicates when the selected temperature is reached. Other features are adjustable ventilation for optimal moisture control, ergonomic push/pull handles and big castors for easy movement. A ScanBox is a Scandinavian designed product made for both back and front of house, especially with the Signature option with the possibility to customize the exterior design. Convection heating is offered as an option.

| Outer Measurement | | Inner Measurement | | |
|-----------------------------------|---------|--|--|--|
| Width | 540 mm | Width | 330 mm | |
| Height | 1605 mm | Height | 561 + 561 mm | |
| Depth | 810 mm | Depth | 553 mm | |
| Capacity & Weight | | | | |
| Capacity | acity | | 12 x 1/1GN with 80 mm distance between runners | |
| Maximum Loading Capacity / Runner | | 9 kg | | |
| Net Weight | | 77 kg | | |
| Volume | | 106 liter / chamber | | |
| Features | | | | |
| Color | | Black (RAL 9005) is standard. Red (RAL 3003) and | | |
| | | Grey (RAL 7042). Free of charge. | | |
| <u>Signature</u> | | Put your logo on the box or wrap it in your pattern. | | |



Construction & Electrics

Interior Anodized aluminium

RackDetachable laser cut U-shaped runners in SSTExteriorFiber glass plastic and aluminum profiles

Door HandleRobust excenter lock. One Grip Handle as an option.Door Opening270° with a magnet to keep door at fixed positionTop Bumper & ChassiStainless Steel. Chassi covered with rubber cladding.

Power Connection 220V-240V / 1 phase / 50-60Hz

Hot

Heating ElementYesConsumption W/A706W / 3,07ATemperature RangeUp to 90°C

ALTERNATIVE

Convection HeatingOptionConsumption W/A830W / 3,6ATemperature RangeUp to 90°C

Functions, Safety & Ergonomics

Digital Display Yes, with temperature reached indicator

Adjustable VentilationYes, open & close to adjust moisture levelTray StopProtects from door scratches & trays moving

Runner Tilt StopExtra safety when loading/unloading the box **Classifications**CB, CE, EMC, RoHS, REACH & IP44

Castors (standard) Ø 160 mm double bearing (2 fixed, 2 swivel w/ brake)

Handles Ergonomic push/pull handles 420mm

Extra Loading Spaces Top bumper keeps extra goods safe on top

Options

Convection Heating Ø 125mm Chromed Castors Humidifier

Central Brake Ø 160mm CKN Castors Customized Spacing for Runners

Card Holders A4/A5/A6 Ø 200mm Chromed Castors Pressed Runners

One Grip Handle Ø 200mm Foam Filled Castors Stainless Steel Interior

One Grip Handle w. Lock Key Ø 400mm Cross Country Castors Stainless Steel Exterior

Tow Bars Ergo Drive+ Motorized Chassi

For detailed information of available options please refer to scanbox.se