





Ergo Line Duo Active Cooling + Active Cooling

Ergo Line Duo AC is a light weight, but robust, cart for holding and transportation of cold food with GN1/1 capacity. Detachable U-shaped runners offer safe handling, easy cleaning and optimal temperature distribution. Infinitely variable temperature setting is performed via digital displays which indicates when the selected temperature is reached. Ergonomic push/pull handles and big castors for easy movement. A ScanBox is a Scandinavian designed product made for both back and front of house, especially with the Signature option with the possibility to customize the exterior design. Compressor cooling is offered as an option.

| Outer Measurement Inner Measurement | | | nt |
|-------------------------------------|---------------|---|---------------|
| Width | 1100 mm | Width | 330 mm |
| Height | 1070 mm | Height | 722 mm |
| Depth | 810 / 910* mm | Depth | 535 / 545* mm |
| Capacity & Weight | | | |
| Capacity | | 16 x 1/1GN with 80 mm distance between runners | |
| Maximum Loading Capacity / Runner | | 9 kg | |
| Net Weight | | 104 kg | |
| Volume | | 127 / 130* liter per chamber | |
| Features | | | |
| Color | | Black (RAL 9005) is standard. Red (RAL 3003) and Grey (RAL 7042). Free of charge. | |
| Signature | | Put your logo on the box or wrap it in your pattern. | |

*Compressor Cooling increases depth to 910 mm



Construction & Electrics

| Interior | Anodized aluminium | |
|---------------------|---|--|
| Rack | Detachable laser cut U-shaped runners in SST | |
| Exterior | Fiber glass plastic and aluminum profiles | |
| Door Handle | One Grip Handle as standard. | |
| Door Opening | 270° with a magnet to keep door at fixed position | |
| Top Bumper & Chassi | Stainless Steel. Chassi covered with rubber cladding. | |
| Power Connection | 220V-240V / 1 phase / 50-60Hz | |

Active Cooling

| Thermoelectric Cooling | Yes |
|------------------------|---------------|
| Consumption W/A | 612W / 2,66A |
| Temperature Range | +3°C to +10°C |
| DB / ΔT | 68 / 23° |
| ALTERNATIVE | |
| Compressor Cooling | Option |
| Consumption W/A | 442W / 1,92A |
| Temperature Range | +3°C to +10°C |
| DB / ΔΤ | 63 / 30° |

Functions, Safety & Ergonomics

| Yes, with temperature reached indicator | |
|--|--|
| No | |
| Protects from door scratches & trays moving | |
| Extra safety when loading/unloading the box | |
| CB, CE, EMC, RoHS, REACH & IP21 | |
| Ø 160 mm double bearing (2 fixed, 2 swivel w/ brake) | |
| Ergonomic push/pull handles 420mm | |
| Top bumper keeps extra goods safe on top | |
| | |

Options

- Compressor Cooling Central Brake Card Holders A4/A5/A6 One Grip Handle One Grip Handle w. Lock Key Tow Bars
- Ø 125mm Chromed Castors
 Ø 160mm CKN Castors
 Ø 200mm Chromed Castors
 Ø 200mm Foam Filled Castors
 Ø 400mm Cross Country Castors
 Ergo Drive+ Motorized Chassi
- Customized Spacing for Runners Pressed Runners Stainless Steel Interior Stainless Steel Exterior

For detailed information of available options please refer to scanbox.se

T +46 (0) 454 30 83 00 **F** +46 (0) 454 30 83 30 **E** info@scanbox.se Visiting Adress ScanBox AB, Ekängsvägen 1 SE-293 40 Olofström, Sweden Post Adress ScanBox AB, P.O. Box 13 SE-293 21 Olofström, Sweden scanbox.se